



## PRODUCT SPECIFICATIONS

<b>Tarp Weights:</b>	32 oz.	27 oz.	22 oz.	18 oz.	10 oz.*
	(comes in 10'W sections – 6"-12" overlap suggested per section)				
	(* comes in 12'W sections – 6" -12" overlap suggested per section)				
<b>Standard Colors:</b>	<b>32 /27 oz.:</b> Tan, Royal Blue, Navy Blue, Red, Forest Green, Burgundy, Black, Tan/Brown, Tan/Royal Blue, Tan/Burgundy, Charcoal Dark Gray.				
	<b>22 oz.:</b> Tan, Royal Blue, Navy Blue, Red, Forest Green, Burgundy, Black, Tan/Brown, Tan/Royal Blue, Gray, Yellow.				
	<b>18 oz.:</b> Tan, Royal Blue, Navy Blue, Red, Forest Green, Burgundy, Black, Gray, Yellow, White, Orange, Kelly Green.				
	<b>10 oz.:</b> Gray.				
<b>Material:</b>	<b>32 /27/22/18 oz.:</b> PVC coated polyester fabric.				
	<b>10 oz.:</b> Woven Reinforced Polyethylene.				
<b>Tear Strength:</b>	135 x 103	125 x 90	90 x 65	90 x 65	76 x 76
	ASTM D2261 (Warp x Filling)				
<b>Tensil Strength:</b>	430 x 410	315 x 300	280 x 270	280 x 270	495 x 340
	ASTM D5034 (Warp x Filling)				
<b>Adhesion:</b>	35 lbs.	35 lbs.	35 lbs.	35 lbs.	N/A
	ASTM D751				
<b>Flame Resistance:</b>	PASS	PASS	PASS	PASS	PASS
	Self Extinguishing Fed Std 191(Method #5903), NFPA 701 (Large Scale), Boston Fire Marshall, California Fire Marshall, Underwriters UL-214 and U.S. MIL-C-20696.				

## MOBILE RACK SPECIFICATIONS

<b>Sizes:</b>	34" W x 12'6" L x 67" H for 10-foot wide covers 34" W x 6'4" L x 67" H for 5-foot wide covers
<b>Capacity:</b>	4800 lbs. of GymShield fabric
<b>Rollers:</b>	2½" Diameter, 14 gauge steel, all with locks to prevent accidental unwinding.
<b>Frame:</b>	Mig welded all steel construction.
<b>Brackets:</b>	Steel with Delrin roller bearings.
<b>Wheels:</b>	8" non-marking urethane swivel types, 2 with foot locks.
<b>Warranty:</b>	2 years.



50 East 42nd Street, 14th Floor  
New York, NY 10017

Toll Free: 800-705-1544 Direct: 212-953-1116 Fax: 212-953-1117  
www.signaturesportsflooring.com sales@signaturesportsflooring.com