



## SIGNAFLEX FLOORING

### MAINTENANCE INSTRUCTIONS

**IMPORTANT:** These instructions supersede any verbal or written instructions from Signature Sports Flooring representatives, and must be followed in order for the warranty to be in effect.

#### GENERAL

- A. Preventative maintenance
  - 1. Because 90% of all dirt in a building comes in on footwear, Signature strongly recommends installing and maintaining entrance matting (preferably permanently installed) at all outdoor entrances (20-30 linear feet for major entrances; less for infrequently used entrances). Doing this will improve indoor air quality, reduce flooring maintenance costs, and lengthen the life of your interior floors.
- B. Safety
  - 1. Always post “Wet floor” and/or “Caution” tape when wet maintenance is going to be performed. Refer to cleaners’ MSDS for Personal Protective Equipment requirements.
- C. Cleaning products
  - 1. Signature recommends products manufactured by JohnsonDiversey Inc., which is ISO 9002 and ISO 14000 certified. Johnson Diversey and TASKI-brand products have over 30 years’ history of outstanding performance worldwide. In using these products, follow the instructions on the label and contact the manufacturer directly if you have questions about their use.
    - a. JohnsonDiversey  
8310 16th Street, P.O. Box 902, Sturtevant, WI 53177-0902  
Email: [www.johnsondiverse.com](http://www.johnsondiverse.com); Tech Support: 1-800-558-2332
    - b. TASKI® Profi can be purchased directly from Signature Sports Flooring (1-800-705-1544).

#### MAINTENANCE

**DO NOT** perform the following on your SignaFlex floor:

- A. Use dust mops treated with oils or silicones.
- B. Scrub floor with hard polyester or hard nylon, steel wool, wire brushes, or abrasive cleaners. These materials can damage the floor and cause undue wear to painted game lines.
- C. Use a green, black, or brown pad to scrub floor with cleaner for any type of cleaning: Initial Cleaning, Daily Cleaning, or Deep Cleaning (detailed below).



**DO** perform the following on your SignaFlex floor:

**A. Initial Cleaning**

1. Sweep and/or dust mop or vacuum (with heavy-duty commercial vacuum) the floor to remove all dirt and grit. Post “wet floor” signs.
  - a. **NOTE: This is the single most important maintenance activity for preserving the floor’s appearance and performance – and typically the most overlooked and omitted.**
2. Thoroughly scrub floor using one of the two cleaners listed below. Dilute products as recommended on label. Use red scrubbing pad, or equivalent scrub brush, with a 175-rpm swing machine or auto scrubber.
  - a. Johnson Wax Professional G.P. Forward
  - b. TASKI® Profi
3. Pick up soiled solution with wet/dry vac or auto scrubber.
4. Rinse floor thoroughly and allow to dry completely.

**B. Daily Cleaning**

1. Sweep and/or dust mop or vacuum (with heavy-duty commercial vacuum) the floor to remove all dirt and grit. Post “wet floor” signs.
  - a. **NOTE: This is the single most important maintenance activity for preserving the floor’s appearance and performance – and typically the most overlooked and omitted.**
2. Thoroughly scrub floor using one of the two cleaners listed below. Dilute products as recommended on label. Use red scrubbing pad, or equivalent scrub brush, with a 175-rpm swing machine or auto scrubber.
  - a. STRIDE® Citrus Neutral Cleaner (which is Green Seal GS-37 certified)
  - b. TASKI® R50
3. Pick up soiled solution with wet/dry vac or auto scrubber.
4. Rinse floor thoroughly and allow to dry completely. As needed: Stubborn heel marks may be removed by using a 175-rpm slow speed machine or auto scrubber, with blue pad, and one of the following cleaners:
  - a. Johnson Wax Professional G.P. Forward
  - b. TASKI® Profi

**C. Deep Cleaning**

1. Conduct deep cleaning as needed and when daily cleaning is not meeting expectations
2. Follow the above Initial Cleaning instructions—with the exception of step 2—using a blue scrubbing pad (not a red pad).

For additional information, please contact JohnsonDiversey Technical Support directly at 1-800-558-2332.

